



AIRWORTHINESS DIRECTIVE

This Airworthiness Directive (AD) is issued pursuant to Canadian Aviation Regulation (CAR) 521.427. No person shall conduct a take-off or permit a take-off to be conducted in an aircraft that is in their legal custody and control, unless the requirements of CAR 605.84 pertaining to ADs are met. Standard 625 - Aircraft Equipment and Maintenance Standards Appendix H provides information concerning alternative means of compliance (AMOC) with ADs.

Number:

CF-2025-54R1

Effective Date:

15 April 2026

ATA:

34

Type Certificate:

A-142

Subject:

Navigation – 5G C-Band wireless Broadband Interference with Radio Altimeter System when operating in Canadian airspace.

Revision:

Supersedes AD CF-2025-54, issued 5 November 2025.

Applicability:

De Havilland Aircraft of Canada (formerly Bombardier Inc.) model DHC-8-100/-200/-300 aeroplanes, all serial numbers, when operating in Canadian airspace.

Compliance:

As indicated below, unless already accomplished.

Background:

De Havilland Aircraft of Canada has determined that 5G C-Band broadband interference can result in erroneous radio altimeter data when operating in Canadian airspace affected by 5G C-Band wireless signals which could affect specific systems.

In July 2023, Innovation, Science and Economic Development Canada (ISED), Canada's spectrum regulator, published Standard Radio System Plans (SRSP)-520 Issue 3 and Radio Standard Specifications (RSS)-192 Issue 5. These publications define the spectrum environment for the 5G C Band in Canada. The spectrum auctions for 5G C-Band in the 3.45 to 3.65 GHz (3.5 GHz) and the 3.65- 3.9 GHz (3.8 GHz) band were completed in 2021 and 2023, respectively. Deployment in the 3.8 GHz band occurred in May 2024. Furthermore, ISED concluded a consultation on noncompetitive local licensing (NCL) framework for operation in the frequency bands of 3.9 to 3.98 GHz.

The frequency bands allocated to these services are close to those used by aeroplanes' radio altimeters (4.2 to 4.4 GHz). Transport Canada (TC) has determined that radio altimeters cannot be relied upon to perform their intended function if they experience interference from wireless broadband operations in the 3.45 to 3.98 GHz (5G C-Band).

Based on ISED's resolutions regarding the Canadian spectrum environment, TC has determined that aeroplanes equipped with radio altimeters deemed compliant with the Federal Aviation Administration (FAA) AD 2023-10-02, are less susceptible to 5G interference in the Canadian environment, considering the existing spectrum mitigations. To protect aviation safety, TC issued AD CF-2024-14, which defines radio altimeter tolerant aeroplanes and mandates limitations of operations with non-tolerant radio altimeter when operating in the entire Canadian airspace.

Transport Canada does not anticipate having the capability to assess the actual risk of interference by tracking 5G deployment locations in Canada. Therefore, to protect aviation safety, this AD mandates limitations that must be applied everywhere 5G deployment is permitted – the entire Canadian airspace.

Given the sunset of certain spectrum mitigations in January 2026 and January 2028, it is not certain that a standard can be established for radio altimeter tolerant aeroplanes to the full scope of 5G emissions permitted in Canada after January 2026. This AD is considered interim action, and further AD action may follow.

As terminating action to maintain safe operation for specific systems, this AD CF-2025-54 requires aeroplanes operating in the Canadian airspace to be configured as Radio Altimeter Tolerant (RAT) aeroplanes.

In order to mitigate the risk of the specific 5G interference effects until the aeroplane is RAT configured; this AD requires placarding of the console and reinforces existing AFM limitations and procedures reiterated in Part I B.

Since AD CF-2025-54 was issued, TC has learned that Service Bulletin (SB) 8-53-86 is applicable to the DHC-8-300 RT-300 single radio altimeter configuration. Table 1 Part II of this AD has been revised to identify this requirement.

This AD CF-2025-54R1 revises Table 1 in Part II of this AD to include SB 8-53-86, introducing structural modifications for the DHC-8-300 RT-300 single radio altimeter installation and, otherwise, maintains the requirements of AD CF-2025-54. This AD CF-2025-54R1 also clarifies that Part I and Part II apply when the aeroplane is operating in Canadian airspace.

Corrective Actions:

For purposes of this AD, the following definitions apply:

Radio Altimeter Tolerant Aeroplane is one for which the radio altimeter, as installed, demonstrates the tolerances for emissions in Part I paragraphs A.1 and A.2. of AD CF-2023-46, dated 26 June 2023, using a method approved by the FAA or TC. Aeroplanes that meet the requirements of the FAA definition of "radio altimeter tolerant airplane", as per Paragraph (g) Definitions of FAA AD 2023-10-02, are considered radio altimeter tolerant aeroplanes.

Non-Radio Altimeter Tolerant Aeroplane is one for which the radio altimeter, as installed, does not demonstrate the tolerances for emissions specified in Part I paragraphs A.1 and A.2. of AD CF-2023-46, dated 26 June 2023. Aeroplanes that meet the requirements of the FAA definition of "non-radio altimeter tolerant airplane", as per Paragraph (g) Definitions of FAA AD 2023-10-02, are considered non-radio altimeter tolerant aeroplanes.

Part I – Mitigating Action – Beta Lockout System and Beta Warning Horn: Applicable to non-radio altimeter tolerant aeroplanes when operating in Canadian airspace:

Within 53 days from the effective date of AD CF-2025-54 (19 November 2025):

- A. Install label Part Number (P/N) 81151129-101 in the cockpit, in the vicinity of the Power Levers in accordance with the accomplishment Instructions in Section 3B Service Bulletin (SB) 8-11-115, Revision A, dated 3 December 2012 or later revisions approved by the Chief, Continuing Airworthiness.
- B. Brief all flight crew of the potential for inhibition of the Beta Lockout System and Warning Horn systems in the presence of 5G wireless interference and the necessity to strictly comply with the following AFM limitations and procedures:
 - i. Existing AFM Engine Airborne Operating Limitation 2.5.8 prohibiting in-flight operation of power levers aft of the Flight Idle.
 - ii. AFM Normal Landing procedure 4.4.1 delaying selection of power levers from Flight Idle to DISC until after touchdown has been positively identified.

Part II – Terminating Action – Radio Altimeter Modification: Applicable to non-radio altimeter tolerant aeroplanes when operating in Canadian Airspace:

Within 53 days from the effective date of AD CF-2025-54 (19 November 2025):

- A. For aeroplanes operating in Canadian airspace, fitted with either a single or dual Honeywell RT-300 radio altimeter model, modify the aeroplane in accordance with the Accomplishment Instructions in Section 3 of the applicable DeHavilland Aircraft of Canada SB(s) listed in Table 1 as applicable, or later revisions of the SB approved by the Chief, Continuing Airworthiness, Transport Canada.
- B. Modifying the aeroplane as defined in Paragraph A. Part II of this AD terminates the requirements specified by Part I of this AD.

TABLE 1 – Applicable SB's by Aeroplane Program

Aeroplane Program	Radio Altimeter	SB Numbers
DHC-8-300	RT-300 Single	<ul style="list-style-type: none"> • 8-34-256E – 23 January 2026 • 8-53-86C – 19 December 2025
DHC-8-300	RT-300 Dual	<ul style="list-style-type: none"> • 8-34-254G – 28 January 2026 • 8-53-87F – 19 December 2025
DHC-8-100/200	RT-300 Single	<ul style="list-style-type: none"> • 8-34-257D – 19 December 2025 • 8-53-90D – 19 December 2025
DHC-8-100/200	RT-300 Dual	<ul style="list-style-type: none"> • 8-34-258B – 5 December 2025 • 8-53-89B – 5 December 2025

Aeroplanes that have been modified in accordance with earlier revisions of these service bulletins meet the intent of this AD.

Authorization:

For the Minister of Transport,

ORIGINAL SIGNED BY

Jenny Young
 Chief, Continuing Airworthiness
 Issued on 1 April 2026

Contact:

Philip Lynch, Continuing Airworthiness, Ottawa, telephone 1-888-663-3639, or e-mail TC.AirworthinessDirectives-Consignesdenavigabilite.TC@tc.gc.ca or any Transport Canada Centre.