COMMONWEALTH OF AUSTRALIA CIVIL AVIATION SAFETY AUTHORITY SCHEDULE OF AIRWORTHINESS DIRECTIVES

Israel Aircraft Industries 1123 and 1124 (Westwind) Series Aeroplanes

AD/IAI-W/1 Maximum Operating Speed - Limitation 1/80

Applicability: All models 1123 and 1124 with S/Nos. 94 to 269.

Requirement: Install in clear view of the pilot a placard as follows, as applicable to model type:

1. For model 1123:

MAXIMUM OPERATING SPEED LIMIT BEL (VMO/MMO) WITH OR WITHOUT IAS

FUEL IN TIP TANKS:

BELOW 22500 FT 314 KTS IAS ABOVE 22500 FT 0.710 M.

BELOW 26000 FT 314 KTS IAS ABOVE 26000 FT 0.765 M.

2. For model 1124:

MAXIMUM OPERATING SPEED LIMIT

WITH AUTOPILOT ENGAGED AND

WITHOUT FUEL IN TIP TANKS:

(VMO/MMO) WITH AUTOPILOT

DISENGAGED:

BELOW 22500 FT 314 KTS

IAS ABOVE 22500 FT 0.710 M.

WITH AUTOPILOT ENGAGED: BELOW 26000 FT 314 KTS

IAS ABOVE 26000 FT 0.765 M.

Compliance: Within 10 hours time in service after 5 December 1979, placard to remain in place

until aeroplane is modified in accordance with SB No. WW23 or SB No. WW24-17

as applicable and Israel CAA AD No. 1007.

Background: A discrepancy in the pattern of rivets installed in the wing root assembly and in the

total strength assumption has been noted by the manufacturer.